

DESICCANT

for Container or Storage

ABSORGEL

is based on the proven ability of Calcium Chloride to aggressively remove moisture from the air.

How the Absorgel works

The Absorgel will start to activate once removed from its sealed package. The Absorgel is easy to use. It can hang within the corrugated recess of the container side panel or be placed horizontally on top of the cargo.

Absorbed moisture is contained by the gelling agent. There is NO liquid water.

Technical specification

Dimension:
Length 1560 mm
Width 130 mm
Depth 20 mm

Working temperature

- 20°C to 90°C
- 4 °F to 194°F

Net weight :

1.0 Kg

Content :

Calcium Chloride
with gelling agent

Why Absorgel ?

- * Easy to install and remove
- * High absorption
- * Prevent moisture damage

ABSORGEL
No liquid water



ABSORGEL
www.absortech.com

Absorbopak Ltd. Contact: Pat Campion

IRELAND

3 Campbell Court, Main Street,
Howth, Dublin 13, Ireland

Tel: +353 (0) 87- 225 0516
Fax: +353 (0) 1-8324419

UK

Wilson Road, South Wigston,
Leicester LE18 4TQ, England

Tel: +44 (0) 11625 81160
Mob: +44 (0) 797 690 1255
Fax: +44(0) 1162 777784

Email: info@absorbopak.com
Web: www.absorbopak.com